

TECHNICAL DATA

# Fluke 700PRV-1 Pressure Relief Valve Kit



## Key features

- Adjustable from 725 to 5800 PSI (50 to 200 bar)
- Preset at 2,900 psi/200 bar
- Repeatability to 10% of nominal setting
- Installs directly into the 700HTP-1 pump

## Product overview: Fluke 700PRV-1 Pressure Relief Valve Kit

The Fluke 700PRV-1 consists of a relief valve settable from 725 to 5800 PSI (50 to 200 bar) to be used with the 700HTP-1 Hydraulic Test Pump. The 1/8" NPT male thread to fits directly into the Fluke 700HTP-1 pressure pump.

To be used with the 700HTP-1 Hydraulic Test Pump. The 700PRV uses a multi-turn adjustment screw to set preload on internal disc springs. This relief valve will protect the most commonly used Fluke pressure modules and pressure instruments from damage due to accidental over-pressurization.

## Specifications: Fluke 700PRV-1 Pressure Relief Valve Kit

| Mechanical and General Specifications |   |
|---------------------------------------|---|
| Size                                  | 1.52 in by 0.62 in diameter (38 mm by 16 mm diameter) |
| Weight                                | 1.6 oz (46 g)   |
| Warranty                              | One year  |



|          |                          |
|----------|--------------------------|
| Material | Type 303 stainless steel |
|----------|--------------------------|

## Ordering information



### **Fluke 700PRV-1**

Fluke 700PRV-1 Pressure Relief Valve Kit

- One adjustable relief valve
- Instruction sheet

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
08/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**