




# 2-VALVE BLOCK MANIFOLD


## Stainless Steel Body, NPT Connections



BBV-0F



BBV-0N



The **SERIES BBV-0** 2-Valve Block Manifold is perfect for use over a broad range of industrial applications including oil refineries, nuclear power stations, petrochemical processing, and more. The Series BBV-0 is forged from 316 stainless steel bar stock and designed to withstand repeated open and close operations. Suited to control oil, water, toxic fluids, chemicals, air, and steam; the 2-valve block manifold has (1) isolate and (1) vent valves. Each valve stem is precision machined with hard seats to reduce operating torque.

### APPLICATION

- Industrial gage or transmitter isolation

### SPECIFICATIONS

**Service:** Compatible liquids, gases, or steam.

**End Connections:** Process connection: 1/2" female NPT; Instrument connection: No flange: 1/2" male NPT; Flange: 1/2" DIN 19213 flange; Vent/test: 1/4" female NPT.

**Wetted Materials:** Body, stem, valve assembly: 316 SS; Stem packing: PTFE.

**Pressure Limit:** 6000 psi (400 bar).

**Temperature Limit:** 464°F (240°C).

**Other Materials:** Handle: 304 SS.

### MODEL CHART

Model	Description
BBV-0F	Flanged 2-valve block manifold
BBV-0N	2-valve block manifold