

+

THREADED ENDS					FLANGED ENDS								
VALVE SIZE	A	B	C	D	E	WEIGHT LBS	VALVE SIZE	FLANGE ANSI	DIMENSIONS, INCHES			WEIGHT LBS	
								A ₁ ⊕	B	C ₁	D		
1/4	5.00	7.62	2.56	5.00	1/2"	11	1/2	150#	9.50	7.62	4.75	5.00	15
3/8	5.00	7.62	2.56	5.00	1/2"	11		300#	9.75	7.62	4.87	5.00	18
1/2	5.00	7.62	2.56	5.00	1/2"	11	3/4	150#	9.50	8.75	4.75	6.87	27
3/4	5.00	8.75	2.62	6.87	1"	20		300#	9.75	8.75	4.87	6.87	30
1	5.00	8.75	2.62	6.87	1"	20	1	150#	9.50	8.75	4.75	6.87	27
1 1/4	7.50	16.75	4.00	9.37	2"	68		300#	9.75	8.75	4.87	6.87	30
1 1/2	7.50	16.75	4.00	9.37	2"	68	1 1/4	150#	13.00	16.75	6.50	9.37	75
2	7.50	16.75	4.00	9.37	2"	68		300#	13.25	16.75	6.62	9.37	81
							1 1/2	150#	13.00	16.75	6.50	9.37	78
								300#	13.25	16.75	6.62	9.37	87
							2	150#	13.00	16.75	6.50	9.37	84
								300#	13.25	16.75	6.62	9.37	90

① NOT TO ANSI

SPECIFICATION DATA	
CUSTOMER _____	SERIAL No. _____
ORDER No. _____	TAG No. _____
VALVE TYPE _____	QTY. _____
BODY _____	
END CONN. _____	
INLET PRESS. _____	MAX. Δ P _____
PRESS. RANGE _____	SET AT _____
VALVE ACTION: RISE IN PRESSURE TO	<input type="checkbox"/> OPEN
	<input type="checkbox"/> CLOSE
VALVE SEAT _____	Cv _____
MISC. _____	
CERTIFIED _____	DATE _____

RICHARDS INDUSTRIES
CINCINNATI, OHIO
U.S.A.

VALVE GROUP _____

FN: MK58	DRAWN BY JLA	DATE 4/30/96
	CHECKED BY	DATE

1/4-2" MARK 58 GLOBE STYLE
PRESSURE REDUCING VALVE

+