

TECHNICAL DATA

Fluke Networks Pro3000™ Probe



Key features

- Loud speaker makes the tone easy to hear through enclosures
- Easy-to-use adjustable volume control dial
- "Quick-twist" tip for easy replacement
- Replacement probe tip stores in battery compartment
- Recessed on/off button

Product overview: Fluke Networks Pro3000™ Probe

The Pro3000™ unfiltered probe, for use on inactive networks, features a loud speaker to hear tone clearly through walls, enclosures and in loud environments. The recessed on/off button helps prevent the probe from accidentally being turned on when stored.


Specifications: Fluke Networks Pro3000™ Probe

| | |
|----------------|--|
| User interface | ON/OFF push button Volume dial Replaceable tip 3.5 mm earphone jack |
| Battery | 9V alkaline |
| Temperature | Operating: -20° C to 60° C, Storage: -40° C to 70° C |



| | |
|-----------------|---|
| Case dimensions | 9.8 in. x 1.6 in. x 1.3 in. (24.9 cm x 4.1 cm x 3.3 cm) |
|-----------------|---|

Ordering information



26100900

The Pro3000™ unfiltered probe, for use on inactive networks, features a loud speaker to hear tone clearly through walls, enclosures and in loud environments. The recessed on/off button helps prevent the probe from accidentally being turned on when stored.

Includes:

- Pro3000™ Analog Probe

Optional accessories

Description

Fluke Networks Pro3000™ Replacement Tip [Replacement tip for Pro3000/3000F series probes.](#)



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2022 Fluke Corporation.
Specifications subject to change without notice.
08/2022

**Modification of this document is not permitted
without written permission from Fluke Corporation.**