

Certificate of Compliance

Certificate Number:

UL-US-L001250-5

Report Reference:

MP618-19790105

Issue Date:

2024-09-05

Issued to:

ASCO, L.P.
160 Park Ave Florham Park, NJ 07932
United States

This certificate confirms that representative samples of:
YIOZ - Valves, Electrically Operated

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 429, 7th Ed., Issue Date: 2013-11-06, Revision Date: 2021-03-19, UL 428B, Edition 2, Issue Date 2022-08-22

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L001250-5
Report reference MP618-19790105
Date 2024-09-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
8266C203, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C215, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C219, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C233, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C239, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C243, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266C247, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266D1, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D101, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D107, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D11, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266D123, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D153, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D161, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D169, may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T, with suffix L or V.	General purpose valves
8266D23, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D47, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D53, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L001250-5
Report reference MP618-19790105
Date 2024-09-05

8266D57, , may be provided with prefix DP, HB, J, JB, JKP, L, M, R, T with suffix L or V.	Safety valves
8266D61, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D69, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D7, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D77, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266D85, , may be provided with prefix DF, HT, J, JB, JKF, L, M, R, T with suffix L or V.	Safety valves
8266G001, G007, G023, G047, G053, G061, G069, G077, G085 followed by V, L or LV1, with or without prefix GP, HT, JB, JKF, JPKF, JKH, JPKH, JBKF, JBKH or L.	Safety valve
8266G011, G057, G2013, G215, G219, G223, G239, G243, G247 followed by V, L or LV1, with or without prefix GP, HB, JB, JKP, JPKP, JKB, JPKB, JBKP, JBKB or L.	Safety valve
8266G101, G107, G123, G153, G161, G169 followed by V, L or LV1, with or without prefix GP, HT, JB, JKF, JPKF, JKH, JPKH, JBKF, JBKH or L.	General-purpose valve



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

