

Type code

Type code

Output signal

P	Output signal Pt100, 4-wire
A	Measuring transducer 4 ... 20 mA, 2-wire

Measuring range

A	-50 ... +150 °C
B	-50 ... +250 °C

Process connection

ZZ	Without process connection
G1	Thread G ¼ B
GE	Thread G ½ B
N4	Thread ¼" NPT
N2	Thread ½" NPT
S1	Clamping connection G ¼ B, CrNi steel clamping ring
SE	Clamping connection G ½ B, CrNi steel clamping ring
S4	Clamping connection ¼" NPT, CrNi steel clamping ring
S2	Clamping connection ½" NPT, CrNi steel clamping ring
P1	Clamping connection G ¼ B, PTFE clamping ring
PE	Clamping connection G ½ B, PTFE clamping ring
P4	Clamping connection ¼" NPT, PTFE clamping ring
P2	Clamping connection ½" NPT, PTFE clamping ring

Installation length / Diameter

0253	25 mm / 3 mm
0503	50 mm / 3 mm
1006	100 mm / 6 mm
1506	150 mm / 6 mm
2506	250 mm / 6 mm
3506	350 mm / 6 mm

Electrical connection / Enclosure rating

G	Cable gland M16 x 1.5, IP 65
P	Cable gland M16 x 1.5, IP 67

Special features of the version

Z	Without special features of the version
G	Oil- and grease-free

TBT -	1								
-------	---	--	--	--	--	--	--	--	--

Not all variants of the type code can be combined!